Amendments to the Claims:

Serial No.: 10/631,916

- 1. (Canceled)
- 2. (Canceled)
- 3. (Canceled)
- 4. (Canceled)
- 5. (Canceled)
- 6. (Canceled)
- 7. (Canceled)
- 8. (Canceled)
- 9. (Canceled)
- 10. (Canceled)
- 11. (Canceled)

Docket No. 5003073.073US1

12. (Canceled)

Serial No.: 10/631,916

- 13. (Currently Amended) A surface treated absorbent material comprising a superabsorbent material comprising consisting essentially of a superabsorbent polymer comprising consisting essentially of
- a) at least about 75% by weight of the superabsorbent polymer of [[a]] an anionic polymer comprising functional groups selected from carboxyl groups, sulfonate groups, sulfonate groups, sulfite groups, and phosphate groups selected from the group of anionic polymer or cationic polymer; and
- b) an internal crosslinking agent based on the polymerizable unsaturated acid group containing monomer[[;]], wherein the superabsorbent polymer has a degree of neutralization of greater than about 25%; wherein elements a) and b) are polymerized and prepared into superabsorbent polymer particles and further comprising the following surface additives to form surface treated superabsorbent polymer particles
 - i) from about 0.5% to about 5% by weight of surface crosslinking agent based on the superabsorbent polymer composition; and
 - ii) from [[0]] <u>about 0.5</u>% to about 5% by weight of a <u>cationic</u> polymeric coating <u>selected from cationic or anionic polymer</u> based on the superabsorbent polymer composition[[.]];

the superabsorbent material having a gel stiffness index of at least about 0.8, said superabsorbent material comprising a cross-linked polymer comprising at least about 75 weight percent anionic polymer, and a surface treatment applied to the superabsorbent material, said

Serial No.: 10/631,916 Docket No. 5003073.073US1

surface treatment comprising a water soluble non-cross-linked polymer comprising at least about 50 weight percent cationic polymer.

- 14. (Original) A surface treated absorbent material as set forth in claim 13 wherein the surface treated absorbent material has a gel bed permeability (GBP) under load as determined by a Gel Bed Permeability Under Load Test of at least about 200x10⁻⁹cm².
- 15. (Original) A surface treated absorbent material as set forth in claim 14 wherein the surface treated absorbent material has a gel bed permeability (GBP) under load as determined by the Gel Bed Permeability Under Load Test of at least about $400 \times 10^{-9} \text{cm}^2$.
- 16. (Original) A surface treated absorbent material as set forth in claim 13 wherein the superabsorbent material has a centrifuge retention capacity (CRC) as determined by a Centrifuge Retention Capacity Test of at least about 20 g/g.
- 17. (Original) A surface treated absorbent material as set forth in claim 13 wherein the superabsorbent material has a centrifuge retention capacity (CRC) as determined by a Centrifuge Retention Capacity Test of at least about 25 g/g.
- 18. (Original) A surface treated absorbent material as set forth in claim 13 wherein the cationic polymer is polyvinyl amine.
 - 19. (Canceled) A surface treated absorbent material as set forth in claim 13 wherein

the concentration of cationic polymer is in the range of about 0.05 to about 5 weight percent of the superabsorbent material.

- 20. (Original) A surface treated absorbent material as set forth in claim 13 wherein the superabsorbent material has a gel stiffness index of at least about 0.85.
- 21. (Original) A surface treated absorbent material as set forth in claim 13 wherein the surface treatment is applied to substantially the entire outer surface of the superabsorbent material.
- 22. (Canceled) A surface treated absorbent material as set forth in claim 13 wherein the water soluble non-cross-linked polymer of the surface treatment comprises at least about 70 weight percent cationic polymer.
- 23. (Original) A surface treated absorbent material as set forth in claim 13 wherein the surface treatment further comprises in the range of about 0.5 to about 5 grams weight of water per 1 gram weight of superabsorbent material.
- 24. (Original) A surface treated absorbent material as set forth in claim 13 wherein the surface treated absorbent material has a free swell gel bed permeability as determined by a Free Swell Gel Bed Permeability Test of at least about 2,000x10⁻⁹cm².

Serial No.: 10/631,916 Docket No. 5003073.073US1

25. (Original) A surface treated absorbent material as set forth in claim 24 wherein the surface treated absorbent material has a gel bed permeability (GBP) under load as determined by a Gel Bed Permeability Under Load Test of at least about 200x10⁻⁹cm². 26. (Canceled) (Canceled) 27. 28. (Canceled) 29. (Canceled) 30. (Canceled) 31. (Canceled) 32. (Canceled) 33. (Canceled)

34.

35.

(Canceled)

(Canceled)

Docket No. 5003073.073US1

- Serial No.: 10/631,916
 - 36. (Canceled)
 - 37. (Canceled)
 - 38. (Canceled)
 - 39. (Canceled)
- 40. (Original) A surface treated absorbent material as set forth in claim 14 wherein the surface treated absorbent material has a gel bed permeability (GBP) under load as determined by the Gel Bed Permeability Under Load Test of at least about $300 \times 10^{-9} \text{cm}^2$.